



Texas Gate Application Form

Applicant Information

Applicant Name
(Individual or Company)

Mailing Address:

Phone Number(s):

Email Address:

Property Information

Legal Land Description (Quarter Section, Township, Range, Meridian):

Municipal Road Allowance Location (Road Name/Number, if applicable):

Road Allowance Type: ☐ Developed ☐ Undeveloped

Purpose and Operational Need

Provide a brief description of the agricultural or livestock operation and the operational need for the Texas gate:

Supporting Documentation (Required)

- ☐ Fabrication Plan (dimensions, materials, structural details)
- ☐ Site Plan (location, road alignment, fencing, access points)



Acknowledgements and Conditions

- The Applicant agrees that all costs for signage, construction, installation, and removal are their responsibility unless otherwise approved by the County.
- The fee payable with each application is per the Master Rates Bylaw, which is updated annually.
- Two (2) Texas Gate Ahead signs (WA-115 complete with posts) 100 m from gate on each side of gate may be required.
- Four (4) Chevrons (WA-36-L & WA-36-R); 2 per side located on gate uprights are required.
- The Texas gate must meet Cypress County design and safety standards pursuant to Policy R21.
- Developed road allowance Texas gates will be maintained by the County.
- Undeveloped road allowance Texas gates will be maintained by the Applicant.
- The Applicant assumes all liability and indemnifies Cypress County.

Applicant Declaration

Applicant Name (Print): _____

Signature: _____

Date: _____

Office Use Only

Application Received Date: _____

Application Complete: ☐ Yes ☐ No

Site Inspection Completed: ☐ Yes ☐ No

Decision: ☐ Approved ☐ Approved with Conditions ☐ Denied

Conditions: _____

Authorized Signature: _____ Date: _____



Texas Gate Construction Specifications

All Texas gates installed on municipal road allowances shall comply with the following minimum construction standards:

Materials

The Texas gate shall be constructed entirely of heavy gauge steel.

- No wood components are permitted under, within, or surrounding the Texas gate structure.

Minimum Dimensions

The Texas gate shall have minimum overall dimensions of:

- 8.0 metres in width, and
- 2.13 metres in length.

Top Surface Construction

- The top surface shall consist of a minimum of twelve (12) heavy-walled steel pipes.
- Each pipe shall have a diameter ranging from 2 $\frac{7}{8}$ inches (2.875") to 3 inches (3.0").

Support Structure

- The top pipes shall be welded to a minimum of six (6) steel I-beams.
- Each I-beam shall be a minimum of 6 inches to 8 inches in size.
- Steel angle iron spacers shall be welded between each top pipe and welded to each I-beam to provide structural rigidity.

Sleeper Assembly

- The I-beams shall be welded to two (2) heavy-walled steel pipes used as sleepers.
- Sleeper pipes shall have a diameter ranging from 8 inches to 10 inches.

Workmanship

- All welding shall be continuous, professional-grade, and suitable for long-term exposure to traffic loading and environmental conditions.
- The finished structure must be capable of safely supporting public vehicular traffic.

Completed forms may be dropped off, returned by mail or emailed to operations@cypress.ab.ca

